



B 21



B 22



B 23



B 24



B 25



B 26



B 27

Dreieplate med 200mm hull for rør-gjennomgang.



B 28



B 29



B 30



B 31



B 32



B 33



B 34



B 35



B 36



B 37



B 38



B 39



B 40





Optional giri 0,4-4,0 RPM

CAT. DONNEE DATA	A	B	C	F	E	D	H	VOLT	GIRI	P1	P2	MF	P3	P4	MT	PESO
SPS 30	200	330	280	262	276	55	425	220	0,5-10	20	11	3	12	2	2	25
SPS 50	300	330	280	262	276	55	425	220	0,5-10	20	11	3	12	2	2	25
SPS 50 HC	300	330	280	262	276	55	425	220	0,5-10	20	11	3	12	2	2	25

Optional volt 110

CAT. DONNEE DATA	A	B	C	F	E	D	H	VOLT	GIRI	P1	P2	MF	P3	P4	MT	PESO
SPS 70	400	500	330	300	340	70	500	220	0,5-12	20	11	3	12	2	2	50
SPS 70/8	400	500	330	300	340	70	500	220	0,5-12	20	11	3	12	2	2	50
SPS 70/8 HC	400	500	330	300	340	70	500	220	0,5-12	20	11	3	12	2	2	50

Optional giri 0,4-4,0 RPM

CAT. DONNEE DATA	A	B	C	F	E	D	H	VOLT	GIRI	P1	P2	MF	P3	P4	MT	PESO
SPS 75	500	500	330	300	340	70	510	220	0,5-12	20	11	3	12	2	2	65
SPS 75/8	500	500	330	300	340	70	510	220	0,5-12	20	11	3	12	2	2	65
SPS 75/8 HC	500	500	330	300	340	70	510	220	0,5-12	20	11	3	12	2	2	65

Optional volt 110

CAT. DONNEE DATA	A	B	C	F	E	D	H	VOLT	GIRI	P1	P2	MF	P3	P4	MT	PESO
SPS 75 HC	500	500	330	300	340	70	510	220	0,5-12	20	11	3	12	2	2	65
SPS 75/8 HC	500	500	330	300	340	70	510	220	0,5-12	20	11	3	12	2	2	65



Optional giri 0,4-4,0 RPM

CAT. DONNEE DATA	A	B	C	F	E	D	H	VOLT	GIRI	P1	P2	MF	P3	P4	MT	PESO
SPS 150	600	500	330	300	340	70	500	220	0,5-12	20	11	3	12	2	2	100
SPS 150/8	600	500	330	300	340	70	500	220	0,5-12	20	11	3	12	2	2	100
SPS 150/8 HC	600	500	330	300	340	70	500	220	0,5-12	20	11	3	12	2	2	100

Optional volt 110

CAT. DONNEE DATA	A	B	C	F	E	D	H	VOLT	GIRI	P1	P2	MF	P3	P4	MT	PESO
SPS 180	700	700	300	300	340	70	510	220	0,5-12	20	11	3	12	2	2	150
SPS 180/8	700	700	300	300	340	70	510	220	0,5-12	20	11	3	12	2	2	150
SPS 180/8 HC	700	700	300	300	340	70	510	220	0,5-12	20	11	3	12	2	2	150



Optional giri 0,4-4,0 RPM

CAT. DONNEE DATA	A	B	C	F	E	D	H	VOLT	GIRI	P1	P2	MF	P3	P4	MT	PESO
SPS 180	700	700	300	300	340	70	510	220	0,5-12	20	11	3	12	2	2	150
SPS 180/8	700	700	300	300	340	70	510	220	0,5-12	20	11	3	12	2	2	150
SPS 180/8 HC	700	700	300	300	340	70	510	220	0,5-12	20	11	3	12	2	2	150

Optional volt 110

CAT. DONNEE DATA	A	B	C	F	E	D	H	VOLT	GIRI	P1	P2	MF	P3	P4	MT	PESO
SPS 180 HC	700	700	300	300	340	70	510	220	0,5-12	20	11	3	12	2	2	150
SPS 180/8 HC	700	700	300	300	340	70	510	220	0,5-12	20	11	3	12	2	2	150

56

Multipass welding

With the CNC at each rotation the system can change all the parameters of different components


