

Gullco International Limited

21568 Alexander Rd.

Cleveland OH 44146 US





Phone: 440-439-8333 • **Fax:** 440-439-3634**Email:** sales@gullco.com • **Website Address:** www.gullco.com**Compare Items****Compact In-shop Welding Electrode Stabilizing Ovens**

These Gullco Stabilizing Ovens have gained international recognition and acceptance based on a variety of quality and performance features including....

- compact, modular design with controls recessed for protection.
- shelves easily removed to accommodate large size loads.
- oven fully insulated to prevent heat loss....pilot light indicates oven operation.
- thermostat control, incorporating on/off switch, maintains oven temperature in 37.8° - 287.8° C range.
- models 125 and 350 feature nesting feet and sockets for safe, easy stacking.

High Temp to 343° C Available on Most Models

Weight capacity depends on electrode length

Items				
	125 Electrode Stabilizing Compact In-Shop Ovens	350 Electrode Stabilizing Compact In-Shop Ovens	350-220 Electrode Stabilizing Compact In-Shop Ovens	1000 Electrode Stabilizing Compact In-Shop Ovens
Capacity	57 kg	159 kg	159 kg	454 kg
Outside Dimensions	407mm x 407mm x 622mm	559mm x 559mm x 622mm	559mm x 559mm x 622mm	1016mm x 768mm x 768mm
Inside Dimensions	209mm x 248mm x 482mm	356mm x 405mm x 482mm	356mm x 405mm x 482mm	610mm x 552mm x 610mm
Unit Weight (approx.)	27 kg	50 kg	50 kg	150 kg
Electrode Size	Up to 457 mm			
Line Cord	2428 mm	2428 mm	None	None
Thermostat	Yes			
Pilot Light	Yes			
Temp. Range	38-288 °C			
Door Latch	Push/Pull			
Stacking	Yes			
Operation	115 or 220 Volt, AC	115 or 220 Volt, AC	115 or 220 Volt, AC	220 / 440 Volt, AC